
# INSTRUMENT

4E



## LIQUIDS REFLECTOMETER

The liquids reflectometer features a horizontal sample geometry and so can accommodate air/liquid surfaces, in addition to air/solid and liquid/solid interfaces. Active vibration isolation minimizes capillary-wave production by the external environment. The instrument will be useful for a wide range of science, including interfacial stud-



ies of biomaterials, polymers, and chemistry involving thin layers of surfactants or other materials on the surfaces of liquids. Data rates and Q-range covered at a single scattering angle setting will be sufficiently high to permit "realtime" kinetic studies on many systems. Timeresolved experiments include investigations of chemical kinetics, solid-state reactions, phase transitions, and chemical reactions in general.

### SPECIFICATIONS

Source- sample distance	13.6 m
Sample- detector distance	1.5 m
Detector size	20 • 20 cm <sup>2</sup>
Detector resolution	1.3 × 1.3 mm <sup>2</sup>
Moderator	coupled supercritical hydrogen
Bandwidth	$\Delta\lambda = 3.5 \text{ Å}$
Wavelength range	2.5 Å < λ < 17.5 Å
Q range (air/liquid)	0 Å <sup>-1</sup> < Q < 0.5 Å <sup>-1</sup>
Q range (air/solid)	0 Å <sup>-1</sup> < Q < 1.5 Å <sup>-1</sup>
Minimum reflectivity	5 x 10 <sup>-10</sup>

#### RECENT SIGNIFICANT EVENTS

**Instrument Construction** 

- Instrument construction is complete.
- The instrument safety review was conducted on May 31, 2006.
- Commissioning will start in July 2006.

#### FOR MORE INFORMATION, CONTACT LIQUIDS REFLECTOMETER STAFF

Instrument Scientist: John Ankner, anknerjf@sns.gov, (865) 576-5122

Lead Engineer: Tim Chae, chaet@sns.gov, (865) 241-6740

Scientific Associate: Tammy McHargue, mchargueta@sns.gov, (865) 576-9036

www.sns.gov/users/instrument\_systems/instruments/elastic/liquid.shtml

